













RUBBER ELEVATOR BELTS

DIN 22102 / 22104 QUALITY - Y

Rubber elevator belts:

- standard quality - normal,
- abrasion-resistant covers,
- impregnated edges,
- antistatic according to ISO 284,
- ozone-resistant,
- both covers smooth.

Operating temperature: -25 to +60°C,
 material temperature: max. +80°C. EU
 production. Belt manufactured in
 accordance with REACH regulations.

		400/3	500/4	630/4	800/5	1000/5	1250/5
	Type	EP 400	EP 500	EP 630	EP 800	EP 1000	EP 1250
	Thickness cover - mm	2/2	2/2	2/2	2/2	2/2	2/2
	Total thickness - mm	6,5	7,5	8,5	9,5	10	11,5
	Weight* - kg/m²	8,1	9,63	10,68	12,38	13,03	13,39
	Number of plies	3	4	4	5	5	5
	Abrasion - mm³	150	150	150	150	150	150
	Shore Hardness - ISO 7619	65	65	65	65	65	65
	Tensile strength min. - MPa	20	20	20	20	20	20
	Min. breaking strength warp - N/mm	400	500	630	800	1000	1250
	Elongation at break min. - %	400	400	400	400	400	400
	Max working elongation: - %	1,5	1,5	2,5	2,5	2,5	2,5
	Cover adhesion min. - N/mm						
	A	4,5	4,5	4,5	4,5	4,5	4,5
	B	4,5	4,5	4,5	4,5	4,5	4,5

* approximate value